# "VIGOROUS"SERIES



## **CARRYING LOAD**

Tyre Mileage Index in %

#20% underloaded

#Normal Load

100%

## **SEASONAL / AMBIENT TEMPERATURES**

 Tyre Mileage Index in %

 Spring
 15°C
 100%

 Summer
 30°C
 80%

 Autumn
 10°C
 100%

 Winter
 0°C
 120%

## **STOP AND ACCELERATION OPERATION**

Tyre Mileage Index in %

Highway


Overland

50%

100%

150%

### TRAILER AXLES





# **VIGOROUS TS 600**

- Mixed highway and freeway for long distance service.
- Special tread compound offers excellent performance of lower heat build-up.

Size	Ply.	Load Index	Speed Rating	
315/80R22.5	20	157/154	М	



# VIGOROUS TS 600+

- Superior driving and braking performance, excellent traction and adhesion, well
- loading capacity.

Size	Ply.	Load Index	Speed Rating
11R22.5	16	146/143	М
11R24.5	16	149/146	M
295/75R22.5*	16	146/143	M



# **VIGOROUS TS 601**

- Mixed highway and freeway.
- Special tread compound offers cut resistance, super grip on wet road.

Size	Ply.	Load Index	Speed Rating	
295/80R22.5	18	152/149	М	-0.0



# **VIGOROUS TS 602**

- Applied for highway, urban and country road.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.

Size	Ply.	Load Index	Speed Rating	
7.50R16LT*	14	122/118	L	
8.25R16LT*	16	128/124	M	



# **VIGOROUS TS 603**

- Applied for highway, urban and country road.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.

Size	Ply.	Load Index	Speed Rating	
12R22.5	18	152/148	М	







# **TS 605**

- Exceptional mileage and resistance to irregular wear.
- Excellent high speed stability and durability.
- Excellent resistance to rib-tearing.





# **TS 606**

- Low rolling resistance enhances fuel economy
- Outstanding safety.
- Excellent ride comfort with low noise.
- Special sipes help resist uneven wear.

Size	Ply.	Load Index	Speed Rating	
11R22.5	16	146/143	М	



# **TS 607**

- Unique tread design for minimized gasoline consumption.
- Horizontal rid design offers the top guiding and stability at high speed service.

Size	Ply.	Load Index	Speed Rating
13R22.5	18	156/150	K



# **TS 608**

- Unique tread design for minimized gasoline consumption.
- Horizontal rid design offers the top guiding and stability at high speed service.

Size	Ply.	Load Index	Speed Rating	
315/70R22.5	18	154/150	М	-00



# **TS 609**

- Wide base single tire for highway transportation.
- Super steel belt carcass construction enhances casing strength and maximizes tire loadcapacity.

Size	Ply.	Load Index	Speed Rating	
385/65R22.5	20	160	К	



# **TS 610**

- Four vertical and Polygonal groove lines enables perfect maneuverability.
- Special shoulder improve tire shoulder durability.

Size	Ply.	Load Index	Speed Rating
385/65R22.5	20	160	K



# **VIGOROUS TD 700**

- Unique tie-bar pattern design offers superior resistance to irregular wearing and block tearing.
- High mileage and speed with lower heat build up.

Size	Ply.	Load Index	Speed Rating	
11R22.5	16	146/143	М	
315/80R22.5	20	157/154	M	-



# **VIGOROUS TD 701**

- Superior braking performance, high abrasion, well heat dispersion, low noise, well resistance to
- impact, superior stability in high-speed running.

Size	Ply.	Load Index	Speed Rating
295/80R22.5	18	152/149	М



# **VIGOROUS TD 702**

- Stone ejectors in the tread prevents stone retention which can lead to casing damage.
- New tread design giving excellent traction.

Size	Ply.	Load Index	Speed Rating	
11R22.5	16	146/143	М	
11R24.5	16	149/146	М	
295/75R22.5*	16	146/143	М	-00



# **TD 703**

- Superior braking performance, high abrasion, well heat dispersion, low noise, well resistance to
- impact, superior stability in high-speed running.

Size	Ply.	Load Index	Speed Rating	
10.00R20	18	149/146	L	
11.00R20	18	152/149	L	
12.00R20	20	152/148	M	
12R22.5	18	156/153	K	-00







# **TD 705**

Superior braking performance, high abrasion, well heat dispersion, low noise, well resistance to

impact, superior stability in high-speed running.





# **TD 706**

Stone ejectors in the tread prevents stone retention which can lead to casing damage.

New tread design giving excellent traction.

Size	Ply.	Load Index	Speed Rating
3R22.5	18	156/150	К



# **TD 707**

Stone ejectors in the tread prevents stone retention which can lead to casing damage.

New tread design giving excellent traction.

Size	Ply.	Load Index	Speed Rating	
315/70R22.5	18	154/150	м	



## MIX ROAD ALL POSITION

# **VIGOROUS TA 800**

Applied for highway, urban and country road.

Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.

Size	Ply.	Load Index	Speed Rating	
11R22.5	16	146/143	М	
315/80R22.5	20	157/154	М	-



# **VIGOROUS TA 801**

Superior anti-irregular wearing performance, excellent stability in running, lownoise, superior

lateral spreads slippery resistance, well heat dispersion.

Size	Ply.	Load Index	Speed Rating	
315/80R22.5	20	157/154	М	



# **TA 800**

Mixed highway and freeway for long distance service.

Special tread compound offers excellent performance of lower heat build-up.

Size	Ply.	Load Index	Speed Rating	
7.50R16LT	14	122/118	L	
8.25R16LT	16	128/124	L	
9.00R20	16	144/142	K	
10.00R20	18	149/146	L	
11.00R20	18	152/149	L	
12.00R20	20	156/153	K	
12.00R24	20	160/157	K	
12R22.5	18	152/148	М	4
13R22.5	18	156/150	K	



# **VIGOROUS TA 802**

All terrain tyres suitable for all position fitment.

Super level of traction.

Resistant to cuts and stone retention.

Size	Ply.	Load Index	Speed Rating	
12R22.5	18	152/148	М	-00



## **TA 803**

High power mixed; Quansi-sovereign tread; Integrative shoulder pattern.

Special tread compound perform well in hot weather.

Size	Ply.	Load Index	Speed Rating	
.00R24	20	160/157	К	-00



# **VIGOROUS TA 805**

All terrain tyres suitable for all position fitment.

Super level of traction.

Resistant to cuts and stone retention.

Size	Ply.	Load Index	Speed Rating
12.00R24	20	160/157	K
325/95R24*	22	162/160	K



# **VIGOROUS TA 806**

All terrain tyres suitable for all position fitment.

Super level of traction.

Resistant to cuts and stone retention.









# **TA 800**+



- Mixed highway and freeway for long distance service.
- Special tread compound offers excellent performance of lower heat build-up.

Size	Ply.	Load Index	Speed Rating
9.00R20	16	144/142	K
10.00R20	18	149/146	K
11.00R20	18	152/149	K
12.00R20	18	160/157	K



# **TA 807**

- Resistance to irregular wear
- Wilder and deeper tread using a special rubber compound designed to extend the life of the tyre.

Size	Ply.	Load Index	Speed Rating
7.50R16LT	14	122/118	L
8.25R16LT	16	128/124	L
9.00R20	16	144/142	K
10.00R20	18	149/146	L
11.00R20	18	152/149	L
12.00R20	20	156/153	K







- Fuel efficient with lower rolling resisitance
- Excellent traction and wet weather handling.
- Wider tread enhanced tyre life.

Size	Ply.	Load Index	Speed Rating	
10.00R20	18	149/146	L	



# **TM 900**

- Fuel efficient with lower rolling resisitance.
- Excellent traction and wet weather handling.
- Wider tread enhanced tyre life.

Size	Ply.	Load Index	Speed Rating
9.00R20	16	144/142	К
10.00R20	18	149/146	L
11.00R20	18	152/149	L
12.00R20	20	156/153	К





# **VIGOROUS TM 901**

- Stone ejectors in the tread prevents stone retention.
- New tread design giving excellent traction and cut resistance.

Size	Ply.	Load Index	Speed Rating
11R22.5*	16	146/143	М
13R22.5*	20	156/150	K
295/80R22.5*	18	152/149	L
315/80R22.5	20	157/154	L



# **TM 902**

- All terrain tyres suitable for all position fitment.
- Super level of traction.
- Resistant to cuts and stone retention.

Size	Ply.	Load Index	Speed Rating
12.00R20	20	156/153	K
13R22.5	18	156/150	K



# **TM 903**

- Stronger driving force; horizontal block pattern provides stronger driving power and braking force.
- Longer service life, excellent loading performance.

Size	Ply.	Load Index	Speed Rating	
12 00R24	20	160/157	к	



# **TM 905**

- Stone ejectors in the tread prevents stone retention.
- New tread design giving excellent traction and cut resistance.









# **TM 906**

- Stone ejectors in the tread prevents stone retention.
- New tread design giving excellent traction and cut resistance.

Size	Ply.	Load Index	Speed Rating
8.25R20LT	16	139/137	K
9.00R20	16	144/142	K
10.00R20	18	149/146	L
11.00R20	18	152/149	L
12.00R20	20	156/153	K



# **TM 907**

- Stone ejectors in the tread prevents stone retention.
- New tread design giving excellent traction and cut resistance.

Size	Ply.	Load Index	Speed Rating
12.00R20	20	156/153	К



# **TM 908**



- Mixed pattern design provides tire with excellent traction and brake performand.
- Open shoulder structure provides tire with good water evacuation as well as anti-hydroplaning.
- Specialized tread formula and optimized design provide tire with excellent anti-puncture and

neat gene	ration ability.			
e)	Ply.	Load Index	Speed Rating	
R20	16	144/142	К	-00



# TM 909



- Applied for bad road conditions including mining application of heavy duty workloads, short haul within 100kms,low speed less than 40kms/h.
- Large lug pattern design provides excellent grip performance, Wear-resistant compounddesign provide super tread life.
- Excelent stab-resistance,anti-eccentric worn,avulsion resistance and tread wear ability.

Size	Ply.	Load Index	Speed Rating	
12.00R20	20	156/153	D	



# **TM 910**



- Applied for bad road conditions including mining application of heavy duty workloads, short haul within 100kms,low speed less than 40kms/h.
- Large lug pattern design provides excellent grip performance, Wear-resistant compounddesign provide super tread life.
- Fycelent stah-resistance anti-eccentric worn

Size	Ply.	Load Index	Speed Rating	
1.00R20	18	152/149	D	



## 315/80R22.5



## 12.00R24



## 11R22.5



## 12R22.5



## 13R22.5



## 295/80R22.5



## 325/95R24



11R24.5



## 295/75R22.5



## 315/70R22.5



## 385/65R22.5







# 7.00R16LT 7.50R16LT 8.25R16LT 8.25R20LT 9.00R20 10.00R20 11.00R20 12.00R20 \*Developing

SAKA TRADING - SAL SECTOR 32 - STREET 49, T: 05 400 008
YOUR RESOURCEFUL PARTNER CHOUEIFAT - LEBANON M: 03 752 445 | 81 81 81 11

INFO@SAKA.COM.LB WWW.SAKA.COM.LB

# TEGHELE

